Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® 134a

MSDS Number : 000000009876

Product Use Description : Refrigerant, Propellant

Company : Honeywell International, Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call : 800-522-8001

+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

16 61

: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : weak

Hazard Summary : Warning! Container under pressure. This product is not

flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Excessive exposure may cause central nervous system effects including drowsiness and dizziness. Excessive exposure may also cause cardiac arrhythmia. Do not breathe vapour. Rapid evaporation of the liquid may cause frostbite. Avoid contact with skin, eyes and

Page 1 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

clothing. At higher temperatures, (>250 C), decomposition products may include hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling

Exposure Limit 2 ppm.

Potential Health Effects

Skin : Avoid skin contact with leaking liquid (danger of frostbite).

May cause frostbite. Irritating to skin.

Eyes : Causes serious eye irritation.

May cause frostbite.

Ingestion : Unlikely route of exposure.

Effects due to ingestion may include:

Gastrointestinal discomfort

Inhalation : Gas reduces oxygen available for breathing.

Causes asphyxiation in high concentrations. The victim will

not realize that he/she is suffocating.

Excessive exposure may cause central nervous system effects including drowsiness and dizziness. Excessive

exposure may also cause cardiac arrhythmia.

Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : CF3CH2F

Chemical nature : Substance

Chemical Name CAS-No. Concentration

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

1,1,1,2-Tetrafluoroethane 811-97-2 99.80 %

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. If breathing is irregular or stopped.

administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do

not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm,

catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.

Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific hazards during : Contents under pressure.

Page 3 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

firefighting This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

In case of fire hazardous decomposition products may be

produced such as: Hydrogen halides Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2) Carbonyl halides

for firefighters

Special protective equipment : In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit.

No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Immediately evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Wear personal protective equipment. Unprotected persons

must be kept away.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing. Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is \geq 19.5%.

Prevent further leakage or spillage if safe to do so. Environmental precautions

The product evaporates readily.

Page 4 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Handle with care.

Avoid inhalation of vapour or mist.

Do not get in eyes, on skin, or on clothing.

Wear personal protective equipment.

Use only in well-ventilated areas.

Pressurized container. Protect from sunlight and do not expose

to temperatures exceeding 50 °C.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

: The product is not flammable.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Storage

Requirements for storage areas and containers

: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Page 5 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control	Upda	Basis
			parameters	te	

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

1,1,1,2- Tetrafluoroethane	811-97-2	TWA : time weighted average	(1,000 ppm)	Honeywell:Limit established by Honeywell International Inc.
-------------------------------	----------	--------------------------------------	-------------	--

1,1,1,2- Tetrafluoroethane	811-97-2	TWA : time weighted average	4,240 mg/m3 (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
-------------------------------	----------	--------------------------------------	----------------------------	------	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : colourless

Odor : weak

pH : Note: neutral

Melting point/freezing point : -101 °C

Boiling point/boiling range : -26.2 °C

Flash point : Note: not applicable

Evaporation rate : > 1

Method: Compared to CCI4.

Lower explosion limit : Note: None

Upper explosion limit : Note: None

Vapor pressure : 5,915 hPa

Page 7 / 13

Honeywell

Genetron® 134a

00000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

at 21.1 °C(70.0 °F)

14,713 hPa

at 54.4 °C(129.9 °F)

Vapor density : 3.5

Density : 1.2 g/cm3

Water solubility : 1.5 g/l

Partition coefficient: n-

octanol/water

: log Pow: 1.06

Note: The product is more soluble in octanol.

Ignition temperature : > 750 °C

Autoignition temperature : > 750 °C

Decomposition temperature : > 250 °C

Note: To avoid thermal decomposition, do not overheat.

Molecular Weight : 102.02 g/mol

Global warming potential

(GWP)

Ozone depletion potential

(ODP)

: 1,300

: 0

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 50 °C. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

Page 8 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials to

avoid

: Finely divided aluminium

Potassium Calcium

Powdered metals

Aluminium Magnesium

Zinc

Hazardous decomposition

products

: Halogenated compounds

Hydrogen fluoride Carbonyl halides Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 500000 ppm

Exposure time: 4 h

Species: rat

Sensitisation : Cardiac sensitization

Species: dogs

Note: No-observed-effect level 50 000 ppm Lowest

observable effect level 75 000 ppm

Repeated dose toxicity : Species: rat

NOEL: 40000 ppm

Genotoxicity in vitro : Note: In vitro tests did not show mutagenic effects

Further information : Note: Vapours are heavier than air and can cause suffocation

by reducing oxygen available for breathing. Rapid evaporation

of the liquid may cause frostbite. Avoid skin contact with

Page 9 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

leaking liquid (danger of frostbite).

SECTION 12. ECOLOGICAL INFORMATION

Further information on ecology

Additional ecological

information

: Accumulation in aquatic organisms is unlikely. This product contains greenhouse gases which may

contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any

residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

: Observe all Federal, State, and Local Environmental Disposal methods

regulations.

Note This product is subject to U.S. Environmental Protection

Agency Clean Air Act Regulations Section 608 in 40 CFR Part

82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3159

> Proper shipping name : 1.1.1.2-Tetrafluoroethane

Class 2.2

Packing group

2.2 Hazard Labels

IATA UN/ID No. : UN 3159

> Description of the goods : 1,1,1,2-Tetrafluoroethane

Class : 2.2 : 2.2 Hazard Labels

Packing instruction (cargo : 200

aircraft)

Packing instruction

(passenger aircraft)

: 200

Page 10 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

: UN 3159 IMDG UN/ID No.

: 1,1,1,2-Tetrafluoroethane Description of the goods

Class : 2.2 Hazard Labels : 2.2 EmS Number : F-C, S-V Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia, Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada, Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)

: All components of this product are on the Canadian DSL list.

Japan, Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Existing Chemicals

Inventory (KECI)

: On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

Act

: On the inventory, or in compliance with the inventory

Chemical Substances

China. Inventory of Existing : On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

Honeywell

Genetron® 134a

00000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

SARA 302 Components : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 Components : SARA 313: This material does not contain any chemical

> components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

New Jersey RTK : 1,1,1,2-Tetrafluoroethane 811-97-2

Pennsylvania RTK : 1,1,1,2-Tetrafluoroethane 811-97-2

WHMIS Classification : A: Compressed Gas

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

Global warming potential : 1,300

Ozone depletion potential : 0

(ODP)

SECTION 16. OTHER INFORMATION

HMIS III **NFPA**

Health hazard 2 : 1 Flammability : 1 1

Page 12 / 13

Honeywell

Genetron® 134a

000000009876

Version 2.5 Revision Date 12/06/2012 Print Date 08/29/2013

Physical Hazard : 0

Instability : 0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 12/15/2009

Prepared by: Honeywell Performance Materials and Technologies Product Stewardship Group